

## **ASSESSMENT**

8 APR 2014

ISO/IEC 17025

Contact person Maria Rådemar SP Chemistry, Materials and Surfaces +46 10 516 51 65 maria.rademar@sp.se

Reference 2014-03-31 3F026536-1

1(1)

Norske Limprodusenters forening v/Moelven Limtre AS Sørlaminering AS Vestlandske Limtre AS Postboks 143 2391 MOELV Norge

## **Assessment of Emission Measurements**

1. Emission measurements have been performed on a laminated timber called Limtre GL 30C Gran according to to "Emission Classification of Building Materials: Protocol for Chemical and Sensory Testing of Building Materials", ver 15.12.2004, test report 3F026536, dated 2014-02-17.

Results of the emission testing:

Compound	Criteria of M1 after 28 days (mg/m²h)	Emission results of Limtre GL 30C Gran after 28 days (mg/m²h)	Pass / Fail criteria
TVOC $(C_6 - C_{16})$	< 0.2	0.040	PASS
Formaldehyde	< 0.05	< 0.033	PASS
Ammonia	< 0.03	< 0.005	PASS
Carcinogenic compounds (IARC C1)	< 0.005	< 0.003	PASS
Not odorous	≥ 0.1	0.8	PASS

The tested product LIMTRE GL 30C GRAN complies with all the requirements of M1.

2. The emission test of formaldehyde can be compared to an emission test according to EN 717-1:2004, E1.

According to EN 14080:2013 the loading factor for laminated timber in a test according to EN 717-1 is 0.3 m<sup>2</sup>/m<sup>3</sup>. The area specific air flow rate becomes 3.3 m<sup>3</sup>/m<sup>2</sup>h. The test is carried out at 45 % RH, in M1 at 50 % RH. After adjustment of this difference (division by 1.09 (ASTM E 1333-96)) the emission of formaldehyde of the tested sample expressed as concentration is conc  $< 0.033 / 3.3 / 1.09 < 0.009 \text{ mg/m}^3$ .

Compound	Criteria of E1 EN 717-1 (mg/m³)	Formaldehyde result of Limtre GL 30C  Gran expressed as concentration according to EN 717-1 (mg/m³)	Pass / Fail criteria
Formaldehyde	< 0.124	< 0.009	PASS

SP Technical Research Institute of Sweden SP Chemistry, Materials and Surfaces - Chemistry

Performed by

Maria Rådemar

Examined by

Marcus Vestergren

SP Technical Research Institute of Sweden

Postal address

Sweden

Box 857 SE-501 15 BORÅS Office location Västeråsen Brinellgatan 4

SE-504 62 BORÅS

Phone / Fax / E-mail

+46 10 516 50 00 +46 33 13 55 02 info@sp.se

Laboratories are accredited by the Swedish Board for Accreditation and Conformity Assessment (SWEDAC) under the terms of Swedish legislation. This report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.